

# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB05/001131

International filing date: 17 March 2005 (17.03.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB  
Number: 0406123.0  
Filing date: 18 March 2004 (18.03.2004)

Date of receipt at the International Bureau: 24 May 2005 (24.05.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland  
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated


27 April 2005



18MAR04 E882118-1 C69640

P01/7700 0.00-0406123.0 NONE

## Patents Form 1/77

Patents Act 1977  
(rule 16)

## Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

## 1. Your reference

AJT/669/MZD

## 2. Patent application number

(The Patent Office will fill this part in)

0406123.0

18 MAR 2004

## 3. Full name, address and postcode of the or of each applicant (underline all surnames)

Vincent MARGANTONIO & Matthew MARGANTONIO  
Brownridge  
Clink Hill  
West Caister  
Great Yarmouth  
Norfolk NR30 5FW (GB)

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

① 8831620001  
② 8831638001

## 4. Title of the invention

MULTIZONE STIMULATION PROCESS IMPROVEMENTS

## 5. Name of your agent (if you have one)

"Address for service" in the United Kingdom  
to which all correspondence should be sent  
(including the postcode)

i.p. 21 Limited  
Norwich Research Park  
Colney  
NORWICH  
NR4 7UT  
United Kingdom (GB)

Patents ADP number (if you know it)

8143653001

## 6. Priority: Complete this section if you are declaring priority from one or more earlier patent applications, filed in the last 12 months.

Country

Priority application number  
(if you know it)Date of filing  
(day / month / year)

## 7. Divisionals, etc: Complete this section only if this application is a divisional application or resulted from an entitlement dispute (see note f)

Number of earlier UK application

Date of filing  
(day / month / year)

## 8. Is a Patents Form 7/77 (Statement of inventorship and of right to grant of a patent) required in support of this request?

Answer YES if:

YES

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

Otherwise answer NO (See note d)

Patents Form 1/77

**Patents Form 1/77**

9. Accompanying documents: A patent application must include a description of the invention. Not counting duplicates, please enter the number of pages of each item accompanying this form:

Continuation sheets of this form 0

Description 7

Claim(s) 1

Abstract 1

Drawing(s) 1

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for a preliminary examination and search (Patents Form 9/77)

Request for a substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature(s)

for i.p. 21 by Andrew Teasdale

Date 18/03/2001

12. Name, daytime telephone number and e-mail address, if any, of person to contact in the United Kingdom

01603 457008

andrewteasdale@ip21.co.uk

**Warning**

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

**Notes**

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered YES in part 8, a Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- Part 7 should only be completed when a divisional application is being made under section 15(4), or when an application is being made under section 8(3), 12(6) or 37(4) following an entitlement dispute. By completing part 7 you are requesting that this application takes the same filing date as an earlier UK application. If you want the new application to have the same priority date(s) as the earlier UK application, you should also complete part 6 with the priority details.

Aug 03

Patents Form 1/77

DUPLICATE

5

10

- 1 -

**MULTIZONE STIMULATION PROCESS IMPROVEMENTS****Field of the Invention**

15

The invention relates to improvements in multizone stimulation processes used in the oil and gas industry.

**Review of the Art**

20

During the production of oil (or gas) a process known as multizone stimulation is often used. This process involves drilling an elongate shaft also known as a well which is then sealed at one end. A down-hole tool, known as a perforating gun, is used to generate perforations in the side walls of the shaft, at a pre-set point. Chemicals are then pumped  
25 into the surrounding rock to break down the structure of the rock strata, such that oil can subsequently be more efficiently removed from the surrounding strata (or area).

Sealants such as polypropylene balls or small flat wax frits - known in the industry as 'diverters' or 'Frac Balls' - are then passed into the chemicals being used, under pressure  
30 such that they pass into the perforations and so seal off the well shaft from the surrounding area. The perforation process is then repeated at further points within the shaft, chemicals introduced as required and the other points sealed off in the same way if required. When oil production is started/resumed from the area, if polypropylene spheres

have been used then they are forced out of their sealing positions (by the release of the retaining pressure) and carried with the flow of the oil to a point where known means are present to enable their removal. If wax frits are used then, due to the increased ambient temperature at the normal depth at which oil wells are located, the frits are released from  
5 their sealing position (by the release of the retaining pressure) such that they are melted by the hot oil and so do not require removal from the resulting flowing oil.

Another process carried out in the oil/gas industry uses the same chemicals to unblock strata, via previously made perforations, which have become blocked during oil  
10 production. Polypropylene balls or wax frits (sealants) are also used in this case but they result in the blockage of the perforations into which the chemicals initially flow such that the subsequent flow of chemicals is directed to other perforations and hence other blocked strata areas. In this way a number of previously blocked areas of strata can be treated before the pressure is released which is keeping the sealants in place, resulting in a  
15 resumption of the flow of oil from the area.

However, due to the small size of the frits used in these processes and their non-uniform shape, they are not readily transported to the area which is required to be sealed off and the process requires a build up of the frits in the perforations (some frits pass through the  
20 perforation) thus resulting in the need to use large quantities of the frits to seal off the perforations.

There are also problems associated with the transfer of the frits down the apparatus used to deliver them to the relevant area. Due to their irregular shape they tend to block the  
25 transfer lines used in the transfer process.

There therefore exists a requirement for a material which can be used in the aforementioned sealing processes which has the shape and resulting flow characteristics of the polypropylene spheres currently used in combination with the beneficial melting  
30 properties associated with the use of wax frits. The current invention seeks to provide a solution which addresses these issues.

Summary of the Invention

In a first aspect, the invention provides a diverter for use in multizone stimulation processes and characterised in that it comprises a ball consisting of wax with an appropriate melting point, size and specific gravity for use in the stimulation process.  
Diverters are also known as Frac Balls.

Preferably the diverter comprises wax and an appropriate diluent.

Preferably the diverter comprises a ball which is spherical.

In a second aspect, the invention provides a method of producing a diverter suitable for use in multizone stimulation processes, the method being characterised by the features,

- a) that the process used to produce the diverters is an injection moulding process;
- b) that the material used in the process is wax with or without any necessary diluent, of a melting point and specific gravity appropriate to the intended use; and
- c) that the mould cavities defining the shape of the moulded products are ball-shaped.

In a third aspect the invention provides a multizone stimulation process comprising the steps of:

- a) chemically treating an area to improve the flow of oil or gas through rock strata;
- b) sealing the chemically treated area by insertion under pressure of diverters into the walls of a well shaft; and
- c) subsequently releasing the diverters to allow oil to flow;

characterised by the use of diverters in the form of wax (or wax-based) balls of an appropriate size, specific gravity and melting point that, on release of the sealing pressure, they melt as they are carried upwards in the oil flow.

4

Included within the scope of the invention is a diverter for use in multizone stimulation processes substantially as described herein with reference to and as illustrated by any appropriate combination of the accompanying drawings.

5

#### Brief Description of the Drawings

Figure 1 is a perspective view of one of the stainless steel block halves that makes up a two-part mould suitable for forming wax spheres.

10

#### Description of the Preferred Embodiment

In this embodiment, wax spheres are produced by injecting into a two-part mould a wax with an appropriate melting point. The spheres described herein are 5/8 of an inch (16mm) or 7/8 of an inch (22mm) in diameter and this particular embodiment uses paraffin wax with a melting point of 155°F.

15

It will be appreciated by those skilled in the art that other waxes with appropriate melting points could also be used such as vegetable waxes and other manufactured and naturally occurring waxes with appropriate melting points. Paraffin wax typically comprises solid saturated hydrocarbons with the molecular formula  $C_nH_{2n+2}$ . Wax is used in the current application as it is inert with respect to the acidic chemicals used in the multizone stimulation process described herein and additionally is soluble in crude oil which is at a temperature above the melting point of the wax.

20

25

The mould half of Figure 1, and its mirror-image complementary half (not illustrated) mould to be used in the process described herein is treated with an appropriate agent to promote release of wax spheres produced, preferably before the two-part mould used herein is assembled.

30

The mould, when assembled, defines one or more (in practice, many) rows of hollow spheres formed within two blocks of stainless steel. Channels (13) are provided within

the blocks such that each hollow sphere 12 is connected to its immediately adjacent neighbouring spheres.

5 Molten wax is forced into the mould under pressure via a single inlet (11) leading into a sphere (15) defined in a central portion of the mould. The wax is then forced by applied pressure along the channels (13) to adjacent hollow spheres. In this way the hollow spheres fill with wax, from the side to which the inlet is connected, to the opposite side which incorporates a series of channels forming outlets (14) through which air contained in the mould is forced out as the molten wax fills the mould. It is important that there are  
10 no air pockets in the formed wax spheres.

The wax is then allowed to cool and the wax spheres then contained within the mould are released by separating the two blocks that form the mould.

- 15 These wax spheres when used in the process of multizone stimulation are required to have a specific gravity similar to or the same as the chemicals used to break down the rock structure. The reason for this is that as the spheres used must be transported with the chemicals being used, if they have a lower specific gravity they will float in the chemical (gel/liquid), if they have a higher specific gravity they will sink in the chemical gel/liquid.
- 20 In either of these cases a problem will be generated in that the spheres are not readily transported to the required areas. The result of this is that larger quantities of wax spheres must be used to seal off the broken down rock structure before starting the multizone stimulation at other points.
- 25 By making the density of the spheres the same as or similar to the chemical fluids being used the spheres are readily transported by the chemicals being used. The specific gravity of the fluids normally used is 0.9, 1.1, 1.2 or 1.3 relative to water at 25°C. Spheres of the appropriate specific gravity are produced by first mixing the wax used with appropriate quantities of diluents such as calcium carbonate and/or talcum powder which are used in a  
30 powdered form. The appropriate ratio of diluent to wax can be determined.

The reason for using these particular diluents is that they are inert with respect to the paraffin wax used herein. Various other materials could be used as diluents such as other aluminosilicates, potassium carbonate, calcium chloride and the like.

- 5 The current process uses a vertically mounted mould which is filled from top to bottom via the inlet (11).

In use, the size of the spheres used is determined by the diameter of the perforations created by the perforating gun in the well wall. A suitable quantity of wax spheres  
10 (typically 150 - 200) is injected into the flow of the chemicals being used (treatment fluid) by means of a transfer/injection gun.

The wax spheres are transported into the perforations in the wall of the well using the chemicals being used to break down the rock strata, the temperature in the well and  
15 immediate area having been reduced below the melting point of the wax being used by the flow of the stimulation chemicals used. The wax spheres are forced into the perforations in the wall of the well under pressure and form a seal such that the multizone stimulation process can be repeated elsewhere - or alternatively, other processes can be carried out. Positive pressure is applied to keep the spheres in place until the multizone stimulation  
20 process or other processes are complete. Release of the applied pressure results in the flow of oil/gas up the drilled shaft. The temperature within the shafts rises as a result of this to a point in excess of the melting point of the wax. The molten wax then dissolves in the oil such that there is not the previous need to manually recover the known propylene spheres from the flow of oil/gas.

25

The paraffin waxes used in the embodiment described herein can be obtained from the following suppliers:

Paraffin waxes with melting points of 155°F, 180°F can be obtained from the following  
30 suppliers;

AUBIN Chemical Solutions, Aberdeen (GB);

RAW Chemical Distribution Limited, Great Yarmouth (GB); and

7

EKGAR & Co (Chemicals) Limited, Reading (GB) who are the distributors for Eastman Chemical Company in the USA.

Paraffin waxes with a melting point of 220°F are available from RAW Chemicals (GB)  
5 and EKGAR & Co (Chemicals) Limited (GB).

10

CLAIMS

1. A diverter for use in multizone stimulation processes and characterised in that it comprises a ball consisting of wax with an appropriate melting point, size and specific gravity for use in the stimulation process.

2. A diverter as claimed in claim 1 comprising wax and an appropriate diluent.

3. A diverter as claimed in either of claim 1 or claim 2 wherein the diverter is spherical.

4. A method of producing a diverter suitable for use in multizone stimulation processes, the method being characterised by the features,

a) that the process used to produce the diverters is an injection moulding process;

b) that the material used in the process is wax with or without any necessary diluent, of a melting point and specific gravity appropriate to the intended use; and

c) that the mould cavities defining the shape of the moulded products are ball-shaped.

5. A multizone stimulation process comprising the steps of:

a) chemically treating an area to improve the flow of oil or gas through rock strata;

b) sealing the chemically treated area by insertion under pressure of diverters into perforations in the wall of a well; and

c) subsequently releasing the diverters to allow oil to flow;

characterised by the use of diverters in the form of wax (or wax-based) balls of an appropriate size, specific gravity and melting point that, on release of the sealing pressure, they melt as they are carried upwards in the oil flow.

6. The invention substantially as described herein with reference to and as illustrated by any appropriate combination of the accompanying drawings.

ABSTRACTMULTIZONE STIMULATION PROCESS IMPROVEMENTS

5

A diverter for use in multizone stimulation processes and characterised in that it comprises a ball consisting of wax with an appropriate melting point, size and specific gravity for use in the stimulation process.

10 Figure 1 should accompany this abstract.



Figure 1

